

Revel M8 SP2 & SP5 Satellite Packs



Features

- Vertically oriented 2-way loudspeakers for 2-channel or surround systems
- Horizontally oriented center channel with table cradle and bracket (SP5 only)
- Micro Ceramic Composite (MCC) diaphragms
- Sophisticated high-frequency waveguides
- Precision dividing networks
- Magnetic shielding for safe placement near electronic devices
- Included mounting hardware
- Three automotive grade high gloss finishes available (black, white, red)

Specifications

REVEL M8 SATELLITE LOUDSPEAKERS	
Frequency Response (+/-3dB)	110Hz – 21kHz
Recommended Amplifier Power Range	10 – 125 Watts
Sensitivity (2.83V @ 1m)	88dB
Nominal Impedance	8 Ohms
Crossover Frequency	2.2kHz
Low-frequency Drivers	Dual 3" (76mm) woofers with MCC cones
Low-frequency Extension	-3dB @ 110Hz; -6dB @ 100Hz; -10dB @ 90Hz
High-frequency Driver	1" (25mm) tweeter with waveguide and MCC dome
External Dimensions (H x W x D)	11 ⁵ / ₈ " x 4 ¹ / ₄ " x 4 ¹ / ₂ " (296mm x 107mm x 113mm)
Net Weight per Speaker	3.45 lbs (1.6kg)

Revel M8 SP2 & SP5 Satellite Packs

